
Novatech®



300 SERIES | ALL PVC - LOW MAINTENANCE

FROM PATIO DOOR TO ENTRANCE DOOR

CHOOSE...





301

Absolute refinement. A sure value.

Welded PVC frame Welded PVC panels

- Recommended for renovation and new construction, residential projects: single family, condos or multi-units.
- Excellent quality and performance.
- Structural transoms and sidelites minimize air & water infiltration.
- Thermally welded frame & panels.
- Maintenance free, all PVC construction with integrated nail fin and easy installation.
- Large glass area and minimal frames in your view.
- Sizes up to 16' x 8' (W x H).
- Tandem wheels for easy and smooth operation.
- Integrated white or satin grey blinds with Low E glass, available.

310

Hurricane protection with maximum light and contemporary look.

Welded PVC frame Welded PVC panels

- The ideal door to protect you from hurricanes. Tested to resist the worst weather conditions.
- 1" thick impact rated, insulated laminated glass units.
- Maintenance free, PVC construction and stainless steel hardware.
- Tandem wheels for easy and smooth operation.



370

The large panels evoke the charm of garden doors.

Welded PVC frame Mechanically assembled PVC panels

- The 370 combines the practicality of a sliding door with the look of a garden door. Arrange your furniture as you wish with no interference inside or out!
- Excellent quality and performance.
- Structural transoms and sidelites minimize air & water infiltration.
- Thermally welded frame & panels.
- Maintenance free, all PVC construction with integrated nail fin and easy installation.
- Sizes up to 16' x 8' (W x H).
- Tandem wheels for easy and smooth operation.
- Integrated white or satin grey blinds with Low E glass, available.

WARRANTY

20 YEAR LIMITED WARRANTY ON UNPAINTED PVC AND WHITE ALUMINUM EXTRUSION


20 YEAR LIMITED WARRANTY ON LOW-E GLASS UNIT (RESIDENTIAL APPLICATION)


10 YEAR LIMITED WARRANTY ON INTEGRATED BLINDS

5 YEAR LIMITED WARRANTY ON HARDWARE

WARRANTY CERTIFICATE AVAILABLE UPON REQUEST

All products come standard with sealed unit with tempered glass and low-conductive spacer





CHOICE OF OPENINGS AND SIZES *Exterior view

X= OPERATING PANEL O= FIXED PANEL

5'	6'	8'	9' & 12'	9' & 12'	10', 12' & 16'
0 X X 0	0 X X 0	0 X X 0	0 X 0 X 0 0 0 0 X	X O X	0 X X 0
59 1/2" x 79 1/2" or 95 1/2"	71 1/2" x 79 1/2" or 95 1/2"	95 1/2" x 79 1/2" or 95 1/2"	107" x 79 1/2" or 95 1/2" 143" x 79 1/2" or 95 1/2"	107 1/2" x 79 1/2" or 95 1/2" 143 1/2" x 79 1/2" or 95 1/2"	116 1/2" x 79 1/2" or 95 1/2" 140 5/8" x 79 1/2" or 95 1/2" 188 11/16" x 79 1/2" ou 95 1/2"

301

ABSOLUTE REFINEMENT. A SURE VALUE

WELDED PVC FRAME | WELDED PVC PANELS



SHOWN WITH BLACK PAINT OPTION

PERFORMANCES

Canadian Standards	Air-tightness	Water-tightness	Wind resistance	Ease of operation	Forced entry
CAN/CGSB-82.1-M89	A3	B3 (B4 optional)	C3	E3	F1 (F2 optional)
Harmonized Standards - 96" x 80"	Air-tightness	Water-tightness	Structure	Overall	
AAMA/WDMA/CSA101/I.S.2/A440-08	PASSED	360 Pa (470 Pa)	DP-50	PG-R50	

Energy efficiency					
RE 35 / U 1,70 Low E 80/70 Surface 3	RE 33 / U 1,70 Low E 80/70 Surface 2				
	SHGC 0,23 / U 0,29 Low E 62/27 Surface 2				





CHOICE OF OPENINGS AND SIZES *Exterior view

X= OPERATING PANEL O= FIXED PANEL

5'	6'	8'	9'	12'
0 X X 0	0 X X 0	0 X X 0	0 X 0	0 X 0
59 1/2" x 79 1/2" or 95 1/2"	71 1/2" x 79 1/2" or 95 1/2"	95 1/2" x 79 1/2" or 95 1/2"	107" x 79 1/2" or 95 1/2"	143" x 79 1/2" or 95 1/2"

HURRICANE PROTECTION WITH MAXIMUM LIGHT AND CONTEMPORARY LOOK




SHOWN WITH BLACK PAINT OPTION

PERFORMANCES

DP-50; Wind Zone 4; IMPACT rated; please contact us for more details

Harmonized standards - 96" x 96" AAMA/WDMA/CSA101/I.S.2/A440-05 / ASTM E1886-05

Testing performed in a laboratory





CHOICE OF OPENINGS AND SIZES *Exterior view

X= OPERATING PANEL O= FIXED PANEL

5'	6'	8'	9' & 12'	9' & 12'	10', 12' & 16'
0 X X 0	0 X X 0	0 X X 0	0 X 0 X 0 0 0 0 X	X O X	0 X X 0
59 3/8" x 79 1/2" or 95 1/2"	71 3/8" x 79 1/2" or 95 1/2"	95 3/8" x 79 1/2" or 95 1/2"		107 1/2" x 79 1/2" or 95 1/2" 139 5/8" x 79 1/2" or 95 1/2"	

THE LARGE PANELS EVOKE THE CHARM OF GARDEN DOORS



PERFORMANCES


SHOWN WITH WHITE INTEGRATED ALUMINUM MINI-BLINDS

Canadian Standards	Air-tightness	Water-tightness	Wind resistance	Ease of operation	Forced entry
CAN/CGSB-82.1-M89	A3	B3 (B4 optional)	C3	E3	F2
Harmonized Standards - 71" x 80"	Air-tightness	Water-tightness	Structure	Overall	
AAMA/WDMA/CSA101/I.S.2/A440-08	PASSED	360 Pa	DP-50	PG-R50	


Energy e	efficiency
RE 26 / U 1,82 Low E 80/70 Surface 3	RE 25 / U 1,82 Low E 80/70 Surface 2
	SHGC 0,18 / U 0,30 Low E 62/27 Surface 2



TRANSOMS AND SIDELITES



GRIDS



OPTIONS CHART

	301	310	370
Transoms	•	_	•
Sidelites	•	_	•
"Desert Sand" extrusions	•	•	•
Paint	•	•	•
Low E glass	•	•	•
Triple glass	•	_	•
Tinted grey or bronze glass	•	•	•
Integrated blinds with Low E glass - White	•	_	•
Integrated blinds with Low E glass - Satin Grey	•	_	•
Grids	•	_	•
Brick mould and sill extension	•	•	•
Sill extension	•	•	•
Nail fin	•	•	•
Security bar	•	•	•
Head Lock	_	_	•
Foot lock	_	_	•
Double-point mortise lock	•	_	•
Signature handle	•	_	•
Keyed lock	•	•	•
Ultra-resistant screen	•	•	•



HANDLES


OPTION: Double-point mortise



"4 IN 1" PVC BRICK MOULD

Signature™

TRUTH



"RENOVATION" PVC BRICK MOULD







novatechgroup.com

DISTRIBUTED BY



EUROPE

ONTARIO

QUÉBEC

USA 5505, 72st Avenue SE, Unit 17 8 quai du Canal, BP83 2070 Codlin Crescent, Unit 1 1 160 Murano Street 100,181st Street 180 Textile Drive, Calgary T2C 3C4 42 302 Roanne Toronto M9W 7J2 Sainte-Julie J3E 0C6 Beauceville G5X 2T1 Ridgeway, Virginia, 24148



